IN THE CLAIMS:

1. (Original): A method of communicating on a communication system having a client terminal connecting a server through a network and collaborating with other client terminals connected to said network, said method comprising the steps of:

    (a) generating an image file in response to specifying an image area by an operator of said client terminal;

    (b) acquiring an image file name from said server;

    (c) converting said image file to generate a predetermined formed compressed image data which has a file name relating to said image file name;

    (d) sending said predetermined formed compressed image data to said server;

    (e) displaying said predetermined formed compressed image data of said server on a Web browser on said client terminal; and

    (f) posting the file name of said predetermined formed compressed image data to the client terminals collaborating with said client terminal.

2. (Original): A method of communicating on a communication system having a client terminal connecting a server through a network, said method comprising the steps of:

    (a) generating an image file in response to specifying image data by a operator of said client terminal;

    (b) determining a unique image file name on said server;

    (c) converting said image file to generate a predetermined formed compresses image data which has a file relating to said unique image file name;

    (d) sending said predetermined formed compressed image data to said server; and

    (e) displaying said predetermined formed compressed image data of said server on a Web browser on said client terminal.

3. (Original): A method of communication on a communication system having a client terminal connecting a server through a network, said method comprising the steps of:

    (a) generating an image file in response to specifying image data by an operator of said client terminal;

(b) converting said image file to generate a predetermined formed compressed image data;

(c) sending said predetermined formed compressed image data to said server;

(d) determining a unique image file name on said server and posting it to said client terminal; and

(e) displaying said predetermined formed compressed image data of said server on a Web browser on said client terminal.

4. (Original): A method of communicating on a communication system having a client terminal connecting with a network and a server connecting with said network and storing a file created by an operator of said client terminal which has a name capable of determining that it was created by said operator, said method comprising the steps of:

(a) receiving a message sent from said client terminal including information capable of identifying said operator;

(b) acquiring the information capable of identifying said operator included in said message;

(c) acquiring the file name of the file created by said operator based on said information capable of identifying said operator;

(d) generating a file list file by inserting said file name into a skeleton file; and

(e) posting the file name of said file list file to said client terminal.

5. (Original): A client terminal connecting a server through a network and collaborating with other client terminals connected to said network, said client terminal comprising:

(a) a screen range selector for specifying a screen range in response to operation for specifying screen range by an operator;

(b) an image file generator for acquiring an image according to said screen range and generating an image file;

(c) a file acquisition for acquiring an original name from said server;

(d) an image file converter for converting said image file to generate a predetermined formed compressed image data;

(e) a file transmitter for sending to said server said predetermined formed compressed image data which has a file name relating to said original name; and

(f) a display division for displaying said predetermined formed compressed image data of said server on a Web browser on said client terminal.

6. (Original): A server connecting a client terminal through a network and storing a file created by an operator of said client terminal which has a file name capable of determining that it was created by said operator, said server comprising:

(a) a message analysis division for receiving a message sent from said client terminal including information capable of identifying said operator and acquiring said information; and

(b) a file list generator for acquiring the file name of the file created by said operator based on said information, generating a file list by inserting said file name into a skeleton file; and posting the file name of said file list file to said client terminal.

7. (Original): A communication system having a first and a second client terminal connecting with a network and a server connecting said first and a second terminal through said network, said communication system comprising:
the first client terminal comprising:

(a1) an image file generator for, in response to operation for specifying a screen range by an operator, generating an image file according to said operation;

(a2) a file name acquisition division for acquiring an original name from said server;

(a3) an image file converter for converting said image file to generate a predetermined formed compressed image data;

(a4) a file transmitter for sending to said server said predetermined formed compressed image data which has a file name relating to said original name; and

(a5) a display division for displaying said predetermined formed compressed image data of said server on a Web browser on said first client terminal and posting the name of said predetermined formed compressed image data to said second client terminal, and

(b) a server comprising a file name generator for generating an original name capable of uniquely identifying said first client terminal in response to a request from said first client terminal and posting it to said first client terminal; and

(c) a second client terminal for displaying said predetermined formed compressed image data of said server on a Web browser on said second client terminal based on the name of said predetermined formed compressed image data sent from said first client terminal.

8. (Original): A storage medium storing a software product for connecting a server through a network and controlling communication performed on a communication system having a client terminal collaborating with other client terminals connected to said network, said software product comprising the program codes for:

(a) directing said client terminal to generate an image file in response to specifying an image area by an operator of said client terminal;

(b) directing said client terminal to acquire an image file name from said server;

(c) directing said client terminal to convert said image file and generate a predetermined formed compressed image data which has a file name relating to said image file name acquired from said server;

(d) directing said client terminal to send predetermined formed compressed image data to said server;

(e) directing said client terminal to display said predetermined formed compressed image data of said server on a Web browser on said client terminal; and

(f) directing said client terminal to post the file name of said predetermined formed compressed image data to the client terminals collaborating with said client terminal.

9. (Original): A storage medium storing a software product for controlling communication performed on a communication system having a client terminal connecting a server through a network, said software product comprising the program codes for:

(a) directing said client terminal to generate an image file in response to specifying image data by an operator of said client terminal;

(b) directing said client terminal to determine a unique image file name on said server;

(c) directing said client terminal to convert said image file and generate a predetermined formed compressed image data which has a file name relating to said image file name acquired from said server;

(d) directing said client terminal to send said predetermined formed compressed image data to said server; and

(e) directing said client terminal to display said predetermined formed compressed image data of said server on a Web browser on said client terminal.

10. (Previously Amended): A storage medium storing a software product for controlling communication performed on a communication system having a client terminal connecting a server through a network, said software product comprising the program codes for:

(a) directing said client terminal to generate an image file in response to specifying image data by an operator of said client terminal;

(b) directing said client terminal to convert said image file and generate a predetermined formed compressed image data;

(c) directing said client terminal to send said predetermined formed compressed image data to said server;

(d) directing said client terminal to determine a unique image file name on said server and post it to said client terminal; and

(e) directing said client terminal to display said predetermined formed compressed image data of said server on a Web browser on said client terminal.

11. (Original): A storage medium storing a software product for controlling communication performed on a communication system having a client terminal connecting with a network and a server connecting with said network and storing a file created by an operator of said client terminal which has a file name capable of

Page 6 of 16
Sakaguchi– 09/439,130

determining that it was created by said operator, said software product comprising the program codes for:

(a) directing said server to receive a message sent from said client terminal including information capable of identifying said operator;

(b) directing said server to acquire the information capable of identifying said operator included in said message;

(c) directing said server to acquire the file name of the file created by said operator based on said information capable of identifying said operator;

(d) directing said server to generate a file list file by inserting said file name into a skeleton file; and

(e) directing said server to post the file name of said file list file to said client terminal.